

Tomlin TSPV Spring-Type Pressure Relief Valve

Tomlin TSPV Spring-Type relief valves are designed for use in high flow, low pressure positive displacement blower applications. NPT connection sizes of 2", 2.5", and 3" are available supporting set point pressures of 1 PSIG to 15 PSIG and flows up to 2223 CFM.

Tomlin TSPV series valves serve as a suitable replacement for the Kunkle model 337 relief valve in most applications.



NPT Connection (inches)	Valve Dimensions (inches)			Capacity (CFM)		
	Depth	Height	Width	@5 PSI	@10 PSI	@15 PSI
2	4.5	6.3	5.0	590	771	856
2.5	5.0	7.8	5.7	933	1193	1862
3	6.1	8.7	6.9	1200	1862	2223

TOMLIN
Equipment Co.



**INDUSTRIAL EQUIPMENT • MAJOR STOCKING DISTRIBUTOR
ENGINEERING • SALES • SERVICE • PARTS**

242 POPLAR STREET • P.O. BOX 8053 • TOLEDO, OH 43605 • (419) 691-3571 • FAX (419) 691-1928
5091 WEST 164TH STREET • CLEVELAND, OHIO 44142 • (216) 265-0666 • FAX (216) 265-0667
1-800-882-1992 (OHIO TOLL FREE) 1-855-691-0621 (MICHIGAN TOLL FREE)
www.tomlinequip.com