

# Tomlin TSVV Spring-Type Vacuum Relief Valve

Tomlin TSVV Spring-Type relief valves are designed for use in high flow, low vacuum positive displacement blower applications. NPT connection sizes of 2", 2.5", and 3" are available supporting vacuum set points of 1"Hg to 28"Hg and flows up to 1224 CFM VAC.

Tomlin TSVV series valves serve as a suitable replacement for the Kunkle model 215V relief valve in most applications.



NPT Connection (inches)	Valve Dimensions (inches)			Temperature (°F)		Capacity (CFM)		
	Depth	Height	Width	Min	Max	@5" Hg	@10" Hg	@15" Hg
2	4.5	5.8	5.0	-20	400	356	430	430
2.5	5.0	7.3	5.7			450	574	574
3	6.1	8.2	6.9			1043	1224	1224

**TOMLIN**  
Equipment Co.



**INDUSTRIAL EQUIPMENT • MAJOR STOCKING DISTRIBUTOR  
ENGINEERING • SALES • SERVICE • PARTS**

242 POPLAR STREET • P.O. BOX 8053 • TOLEDO, OH 43605 • (419) 691-3571 • FAX (419) 691-1928  
5091 WEST 164TH STREET • CLEVELAND, OHIO 44142 • (216) 265-0666 • FAX (216) 265-0667  
1-800-882-1992 (OHIO TOLL FREE) 1-855-691-0621 (MICHIGAN TOLL FREE)  
[www.tomlinequip.com](http://www.tomlinequip.com)