



INDUSTRIAL EQUIPMENT • MAJOR STOCKING DISTRIBUTOR
ENGINEERING • SALES • SERVICE • PARTS
 242 POPLAR STREET • P.O. BOX 8053 • TOLEDO, OH 43605 • (419) 691-3571 • FAX (419) 691-1928
 5091 WEST 164TH STREET • CLEVELAND, OHIO 44142 • (216) 265-0666 • FAX (216) 265-0667
 1-800-882-1992 (OHIO TOLL FREE) 1-855-691-0621 (MICHIGAN TOLL FREE)
 www.tomlinequip.com

TOMLIN GOLD PD HT **POSITIVE DISPLACEMENT BLOWER LUBRICANT**

Tomlin Gold PD HT is a synthetic lubricant designed to provide excellent performance in all types of positive displacement blowers. The higher viscosity in Tomlin Gold PD HT provides increased anti-wear protection over Tomlin Gold PD in blowers running at higher temperatures.

The PAO base fluid in Tomlin Gold PD HT offers many performance advantages:

- ◆ Extended lubricant life which allows for fewer oil changes and less used oil disposal.
- ◆ Excellent film strength
- ◆ High flash point to help reduce fire hazards.
- ◆ Low evaporation rate to help increase service life.
- ◆ Low pour point for easy operation in cold weather.
- ◆ Superior high temperature stability relative to petroleum oils.
- ◆ Excellent materials compatibility with plastic and rubber parts.

Typical Properties

		<u>ASTM Method</u>	<u>Tomlin Gold</u> <u>PD HT</u>
ISO Viscosity Grade			320
Viscosity, cSt.	40°C	D445	317
	100°C		35.0
Viscosity Index			156
Pour Point	°C/ °F	D97	-33/-27
Flash Point	°C/ °F	D92	270/518
Evaporation %	210°F	D972	<1
Copper Corrosion	212°F	D130	1B
Rust		D665	Pass
Specific Gravity		D1298	0.88