



		6*FLG	8*FLG				
OPENING		6.00	8.00	UNIT			
BOLT CIRCLE		9.50	11.75	SIZE			
FLANGE OD.		11.00	13.50	APPROX. OIL CAP.			
NO. TAPPED HOLES		8	8	6"	28.3 FL OZ	52.1 FL OZ	6.00
SIZE HOLES		3/4-10	3/4-10		7"	32.3 FL OZ	59.5 FL OZ
TAP DEPTH		1.13	1.13				

FRAME SIZE	A	B	C	D	E	E'	F	G	J	K	L	M	N	O	O'	P	R	U	V	KEYWAY	W	W'	AA	AB	AD	AE	AF	AG	APPROX WEIGHT
65	11.00	10.00	18.38	8.75	1.00	4.00	3.81	.38	5.38	2.13	3.00	5.63	3.56	21.63	15.13	12.75	11.75	1.375	2.75	.312x.156	3"NPT	3"NPT	6.38	9.88	3.44	8.00	19.75	17.00	245 LBS
68	"	13.00	21.38	"	"	"	5.81	"	"	"	"	7.13	3.69	"	"	"	"	"	"	"	5"NPT	5"NPT	"	"	"	"	"	"	285 LBS
615	"	20.00	28.38	"	"	"	8.81	"	"	"	"	10.63	"	"	16.25	15.00	"	"	"	"	6*FLG	6*FLG	7.50	"	"	"	"	"	425 LBS

W-INLET
 W'-DISCHARGE
 AD-SHEAVE WIDTH
 AE-SHEAVE DIA.
 ALL DIM. IN INCHES

TOMLIN
Equipment Co.
 Since 1978
INDUSTRIAL EQUIPMENT • MAJOR STOCKING DISTRIBUTOR
ENGINEERING • SALES • SERVICE • PARTS
 232 POPULAR STREET • P.O. BOX 8083 • TOLEDO, OH 43605 • (419) 691-3571 • FAX (419) 691-1938
 5091 WEST 164TH STREET, CLEVELAND, OHIO 44142 • (216) 285-0668 • FAX (216) 285-0667
 1-800-822-1892 (OHIO TOLL FREE) • www.tomlinquip.com

MFG. REF.	CONFIDENTIAL	REVISIONS	BY	DATE	CHANGE NOTICE	CHKD.	APP.	DATE	DO NOT SCALE FOR DIMENSIONS ALL DIMENSIONS SHOWN IN BRACKETS () ARE MILLIMETERS	ORDER No.	UNIVERSAL RAI BLOWER		
THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION OF ROOTS DIVISION, DRESSER INDUSTRIES, INC. IT SHALL BE HELD IN STRICTEST CONFIDENCE, AND BE USED ONLY IN CONJUNCTION WITH ROOTS DIVISION BUSINESS.								<p align="center">ROOTS™</p> <p align="center">DIMENSIONAL TOLERANCES UNLESS OTHERWISE SPECIFIED: FINISHED DIMENSIONS TWO PLACE DECIMALS 0.00-0.499 FRACTIONAL—1/64 THREE PLACE DECIMALS 0.500-1.999</p>				62753021	REV G
REF: EP938	CONCENTRICITY	G REF 'F' DIM ON 68		RDR	6459V	SCALE						CAD FILE / DIRECTORY	
FLATNESS	PERPENDICULARITY	F BOLTS CLARIFIED		DB									
ANGULARITY	PROFILE OF LINE												
PARALLELISM	PROFILE OF A SURFACE												
TRUE POSITION	DIAMETER												
STRAIGHTNESS	FINISH IN MICRO INCHES												